MEMBERS MERICAN CHEMICAL SOCIETY STM INTERNATIONAL MERICAN SOCIETY OF MATERIALS P.O. BOX 152837, DALLAS, TEXAS 75315 1323 WALL ST, DALLAS, TEXAS 75215 PHONE 214/565-0593 FAX 214/565-1094

**Consultants and Technologists Chemical and Petroleum Chemists** 

> MEMBERS AMERICAN NATIONAL STANDARDS INSTITUTE AMERICAN SOCIETY FOR QUALITY CONTROL FEDERATION OF SOCIETIES FOR COATINGS TECHNOLOGY

Submitted by: Tiger Drylac U.S.A., Inc. 110 Southgate Drive Guelph, ON, CA N1G 4P5

Attn: Dan Bloden

## REPORT

# Sample:

Organic Coated aluminum extrusions Coating: 075/90102 Production Date: Not provided. Cure: Not provided. Pre-treatment: Not provided. Drawing: panels

## A. PROCEDURE

Submitted sample was tested for informational purposes according to AAMA 2605-17, "Voluntary Specification, Performance Requirements and Test procedures for Superior Performing Organic Coatings on Aluminum Extrusions and Panels," Section 8.1 through 8.8.2, with the following results:

#### B. REPORT

Test	Results	AAMA 2605-17 Specification Requirements
8.1 Color Uniformity (ASTM D2244)	Standard	Standard
8.2 Specular Gloss (ASTM D523)	45.8	As reported
8.3 Dry Film Hardness (ASTM D3363)	Pass F	F hardness and no film rupture
8.4 Film Adhesion (ASTM D33330) 8.4.1.1 Dry	Pass	
	None	No removal of film from substrate
8.4.1.2 Wet	None	No removal of film from substrate
8.4.1.3 Boiling Water	None	No removal of film from substrate

THE ANALYSIS OF THE ABOVE SAMPLE OR SAMPLES DO NOT IMPLY AN ENDORSEMENT. THIS REPORT OR ANY PART THEREOF MAY NOT BE REPRODUCED OR USED FOR ADVERTISING PURPOSES WITHOUT OUR EXPRESS WRITTEN CONSENT.



DALLAS LABORATORIES, INC.

Date: October 24, 2017

Report No.: 49961-5 P.O. No.: 4580005027

Tiger Drylac U.S.A., Inc. October 24, 2017 Page 2 – Report No. 49961-5

		-
Test	<u>Results</u>	AAMA 2605-17 Specification Requirements
8.5 Impact Resistance (ASTM D3359)	Pass None	No removal of film from substrate
8.6 Abrasion Resistance (ASTM D968)	Pass (>ACV 40)	ACV 40 minimum
8.7 Chemical Resistance 8.7.1 Muriatic Acid	Pass None	No Blistering or Visible Change
8.7.2 Mortar	None	No Blistering or Visible Change
8.7.3 Nitric Acid	Pass (Delta E = 0.87)	Hunter, Delta E = 5 maximum
8.7.4 Detergent	None	No Film Adhesion Loss or Visible Change
8.7.5 Window Cleaner Resistance	None	No blistering or noticeable change in appearance and no film loss
8.8 Corrosion Resistance 8.7.1 Humidity (ASTM D2247)	Pass (No blisters)	Not greater than Few & No. 8
8.8.2 Salt spray (ASTM G85 A5)	Pass	
Scribe Field	10 10	7 Minimum rating 8 Minimum rating

Date Testing Started: 4/28/17 Date Testing Completed: 10/24/17 Date Test Report Expires: N/A Sampled by: N/A

Testing Conducted at: Dallas Laboratories, Inc., 1323 Wall St., Dallas, TX 75215

The test results indicate that the sample tested **for informational purposes** is in compliance with the **specified** performance requirements of AAMA 2605-17 for Superior Performing Organic Coatings on Aluminum Extrusions and Panels.

DALLAS LABORATORIES, INC.

Kevan W, Jones, Vice President

Analyst: GF KWJ: js