

Gloss Killer 44/00006

A POWDER MATTE AGENT FOR POST-ADDITION TO
SMOOTH FLOW POWDER COATINGS

Typical application

- use for interior applications for all TIGER powder series without limitation
- for exterior application use only in conjunction with series 59, 47 and 44

DO NOT use for architectural applications

Product details

Standard Packaging in 20 kg cartons
Minipack 2,5 kg

Storage Stability Use before: see printed date on product label; at no more than 25 °C, avoid direct and extended heat exposure

(The shelf life of custom made blanket orders or other stock agreements which by their nature are stored over longer periods is determined by the original production date.)

Features

- achieves continuous matting from 30 - 60 gloss*

*Gloss level acc. to ISO 2813/60° angle

Finish | Colors

- semi-matte:
add 10 % to 20 % to the powder coating
- matte:
add 20 % to 30 % to the powder coating

Concentration

Mix only 10 % to 50 % of the Gloss Killer agent to the powder coating. Any mix in excess of 30 % to 50 % may result in a weakened hiding power.

Prior to further processing it is required that the buyer and/or user verifies the optimum mixing ratio and the suitability of processes or applications.

Use

The Gloss Killer is dry blended to the powder coating. While mixing of bigger quantities may be done using drum or roll mixers, smaller quantities may be mixed manually.

Please note, that this is polyurethane-based product adhering to the relevant cure agenda is imperative (for more information please see product data sheet 1154).

Processing instructions

The guidelines for application (datasheet 1213) must be strictly observed.

The Product Data Sheets, Technical Information Sheets and the guidelines for application each in their latest version, available as a download at www.tiger-coatings.com.

Disclaimer

Our verbal and written recommendations for the use of our products are based upon experience and in accordance with present technological standards. These are given in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of our products for the intended application. We warrant that our products are free of flaws and defects to the extent as stipulated in our Terms of Delivery and Payment.

As a part of our product information program each of our Product Data Sheets are periodically updated, so that the latest version shall prevail. Therefore, please visit the download area of www.tiger-coatings.com to make sure you have the most current version of this Product Data Sheet. The information in our Product Data Sheets is subject to change without notification.

This Product Data Sheet substitutes any and all previous Product Data Sheets and notes for customers published on this subject matter and is only intended to give a general product overview. Please request specific information for products outside of our standard product list (latest version).

The Technical Information Sheets and the Terms of Delivery and Payment each in their latest version, available as a download at www.tiger-coatings.com, form an integral part of this Product Data Sheet.

certified according to
EN ISO 9001 / 14001
IATF 16949



TIGER Coatings GmbH & Co. KG
Negrellistrasse 36 | 4600 Wels | Austria
T +43 / (0)7242 / 400-0
E powdercoatings@tiger-coatings.com
W www.tiger-coatings.com

44/00006