

UV Heavy Duty Flex Ink Series 140/4

Properties

Viscosity	25 °C 50 °C	24-28 mPas 8-11 mPas
Surface tension	25 °C	22-26 dyn/cm
UV dose for hardening with a Hg lamp (type H)		250-500 mJ/cm ²

Colors

- Series 140/41200 yellow
- Series 140/41300 magenta
- Series 140/41400 cyan
- Series 140/41800 black

Shelf life

- 9 months for storage between 15 and 35°C.

Package sizes

- 1 l PE bottles (black)
- 5 l PE cubitainer (black)
- Other package sizes are available on request.

Recommended cleaning and flushing fluid

TIGER Flush 151/00001

Applications

TIGER Heavy Duty Flex Inks are acrylate-based UV-curing systems that can be used to coat a wide range of substrates, such as coated coil coating plates, which call for strength and a rugged finish. These inks were developed for use in DOD Piezo printing heads.

The inks distinguish themselves through outstanding wet and dry adhesion on a wide range of substrates. Before application of the inks, the surface must be cleaned carefully to ensure that the surface is dust and grease-free. After printing on the pre-treated surface, the finished substrate/surfaces can be used immediately or further processed.

Although the printed ink coatings offer outstanding chemical and mechanical durability, these can be deformed in bending processes. To protect against dirt and grime during the bending process, we recommend that you apply protective films.

T-bend test

acc. to DIN EN 13523

Type of test results	
T0	Light micro cracks formed; not visible to naked eye
T0.5	No cracks
T1	No cracks

Printing conditions

The inks can be processed at up to 55 °C. The necessary UV dose is oriented according to the printed layer thickness, whereby the previously specified 250-500 mJ/cm² corresponds to the typical radiation dose of a non-doped mercury vapor lamp of type H with a coating thickness of 10-15 µm. Better hardening results can be achieved in special cases with doped UV sources (iron or gallium) since the UV radiation emitted covers a larger wavelength range.

Compatibility of materials

Compatible materials:

- PP
- PE (HD + LD)
- Stainless steel
- PTFE
- EPDM rubber
- Plasterboard box
- MDF sheets
- Particle boards
- Aluminum boards
-

Incompatible materials:

- PVC
- Butyl rubber
- Brass
- Viton®
- Nitrile plastics
- Polyurethane rubber
- Neoprene

Disclaimer

Our verbal and written recommendations for the use of our products are based upon experience to the best of our knowledge in accordance with present technological standards. These are given in order to support the buyer or user. They are non-binding and do not constitute any contractual legal relationship or additional obligation from the purchase agreement. They do not release the purchaser from verifying the suitability of our products for the intended application at his own responsibility. We warrant that our products are free of flaws and defects to the extent as stipulated in our Terms of Delivery and Payment.

As part of our duty to inform, we modify our product information periodically according to technical progress. Therefore the most recent valid version of this information is applicable and is available at any time from the Download area at www.tiger-coatings.com. TIGER Coatings GmbH & Co. KG reserves the right to make changes to the product data sheet without written notification.

This Product Data Sheet substitutes any and all previous Product Data Sheets and notes for customers published on this subject matter and is only intended to give a general product overview. When using a product not included in our standard product line according to the standard product list (last valid version), the corresponding Product Data Sheet must be requested.

Our technical notes and the general Terms of Delivery and Payment, the most recent version of which you can call up at any time at www.tiger-coatings.com in the download area, are an integral component of this data sheet.

certified according to
EN ISO 9001 / 14001



TIGER Coatings GmbH & Co. KG
Negrellistrasse 36 | 4600 Wels | Austria
T +43 / (0)7242 / 400-0
F +43 / (0)7242 / 650 08
E powdercoatings@tiger-coatings.com
W www.tiger-coatings.com